



Technical Specifications HOT MELT ADHESIVE 100

Product Name

Tece Hot Melt 100 (THM 100) Transparent Hot Melt

Producer

TECE Dekor A.S.

BOSB 75. Yil Bulvari No:12 Nilufer / Bursa / Turkey

Tel : +90 224 242 2100(pbx)

Fax : +90 224 243 8525

Description

- Hot melt adhesive is special glue which is used during the application of edgebanding to the panel in edgebanding machines.
- This adhesive can be used for **PVC , ABS , HYBRID** and **Veneer edgebanding** application.
- The panel can be plywood, MDF, or Chipboard.

Specifications

Color : It can be white, natural wood color, black or another other color requested by the customer.

Machinery : This hot melt has been used on many kinds of edgebanding machines. From Homag to SCM, from Turanlar to other brands in the world. All results have been satisfactory as long as the application method is right.

View : Solid round pellets.

Application Temperature

180-200 oC should be set in the edgebanding machine.

Technical Specifications

Viscosity (CPS) : 65.000 mPa.s at 200 °C

Softening point : 100°C±3°C

Machine Feed Speed : 20-30 meter / minute

Machine Feed Speed : 20-30 meter / minute

Packaging

20 kg Plastic bucket

Storage

Dry and cool area, it can be stored for 12 months period.

